



BUILDING SEALANT

Date:02/10/06

Page 1 of 1

Technical Data:

Base	Polybutene
Consistency	Stable Paste
Skin formation	Within 15 min (20°C/65% R.H.)
Specific Gravity	1,70g/ml
Temperature Resistance	-20°C to +80°C

Product:

Building Sealant is a high-quality, plastic, one-component sealant based on polybutene.

Characteristics:

- Very easily applied
- Forms an elastic straight skin
- Paintable after 24 hours
- Does not stain on porous surfaces
- Universal adhesion

Applications:

- All joints with small movement (max 7%)
- Filling sealant
- Glazing in greenhouses
- Joints between brickwork and window- or doorframes

Packaging:

Colour: white, grey

Packaging: cartridges 300ml, on request: sausages 300ml, 600ml, drums 30kg

Shelflife:

Twelve months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°.

Surfaces:

Type: all usual building substrates

State of Surface: clean, dry, free of dust and grease

Preparation: powdery surfaces have to be fixated

We recommend a preliminary compatibility test.

Joint Size:

Minimum Width: 5mm

Maximum Width: 20mm

Minimum Depth: 5mm

Recommandation: depth = width

Application:

Method: spatula, manual and pneumatical caulking gun

Application temperature: +1°C to +30°C

Clean: with white spirit immediately after use

Health- and Safety Recommendation:

Apply the usual industrial hygiene.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.