



MOUNTING ADHESIVE

Date: 22/04/05

Page 1 of 1

Technical Data:

| | |
|------------------------|------------------------------------|
| Base | Synthetic rubber (neoprene) |
| Consistency | Paste |
| Curing System | Physical drying and cristalization |
| Specific Gravity | 1,1g/ml |
| Open Time* | 5 min |
| Curing Time* | 20 min (initial strength), 24-48h |
| Quantity to be applied | Approx. 200ml/m ² |

* This can vary according to environmental circumstances such as temperature, humidity, substrate etc.

Product:

Mounting Adhesive is an instant grab, high strength construction adhesive. It can be used for the bonding of plinths, wall panels, ceramic tiles, decorative elements made from many different substrates onto porous and non porous surfaces. Due to its gap-filling characteristics it can be used on uneven surfaces.

Characteristics:

- Excellent initial grab
- Very fast powerful bonding
- Thick body for effective gap-filling properties when bonding uneven surfaces
- Direct application onto one substrate
- Replaces nails and screws
- Waterproof

Applications:

- To fix battens, window sills, skirting boards, coving, plasterboard
- Glueing carpet grippers, edge strips and stair nosings
- Bonding of wall and floor boards, window frames and partitions
- To repair loose tiles

Packaging:

Colour: yellowish

Packaging: cartridges 300ml, on request tins of 1l

Shelflife:

Twelve months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°.

Surfaces:

Type: all surfaces, except PS, PP and PE

State of Surface: clean, dry, free of dust and grease
We recommend a preliminary compatibility test.

Application:

Method: caulking pistol. Extrude a bead onto one surface in strips or dabs. Always apply adhesive to the edge of components. Press the surfaces together immediately. Batten down with a hammer. Support may be required on a vertical fixing or for heavy components. For the bonding of wall panels and other heavy materials use the transfer method: press components together and release for max. 5 min. Return parts together and batten down with a rubber hammer. If necessary support until adhesive is completely cured (approx. 24-48 hours).

Application temperature: +5°C to +35°C

Clean: with white spirit, acetone

Repair: with Mounting Adhesive

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.