



PRIMER 150

Date:01/02/05

Page 1 of 2

Product Description :

Primer 150 is an universal primer for porous surfaces to be used with silicone sealants and sealants based on MS Polymers.

Characteristics :

- Liquid, easy application
- Suitable for silicones and hybrid sealants

Applications :

- All porous surfaces

Application Examples :

- Surfaces of expansion joints
- Joint surfaces of porous materials with high water exposure

Packaging and Colours :

Colours : Transparent
Packaging : Metal tin of 250ml and 1l

Shelflife :

Twelve months in an unopened packaging in a dry and cool storage place at temperatures between +5°C and + 25°C.

Technical Data :

Base : Synthetic resins
Consistency : Liquid
Curing System : Physical drying
Drying Time : Approx. 60 min (20°C/65 % R.H.)
Specific Gravity : 0.93g/ml
Flashpoint : 8°C
Quantity to be applied : Approx. 5 m²/liter

Surfaces :

Substrate : All porous surfaces
State of Surface : Clean, dry, free of dust and grease

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.



PRIMER 150

Date:01/02/05

Page 2 of 2

Application :

Application Method :	Use brush
Application Temperature:	+ 5°C to + 25°C
Clean with :	White Spirit immediatly after application
Recommendation :	After application wait 60 minutes at least and 4 hours at most before applying a sealant

Transport Information :

Road :	ADR :	3.3b
Maritime :	IMDG :	3.2 - Packing Group II
		EMS 3-07 - MFAG 310
Air :	ICAO/IATA-DGR :	Pkg Group III - Class 3
UN Number :		1294

Labelling :

Symbol :	Xn - harmful - F - flammable
R-Sentences :	11, 20
S-Sentences :	16-25-29-33
Contains :	Toluene - Butanol

Safety Measures :

Apply the usual industrial hygiene.
Wear gloves and goggles

Remarks :

If the maximum waiting time of 4 hours has passed before application of the sealant, apply a new layer of Primer 150.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.