



SILICONE REMOVER

Date:01/02/05

Page 1 of 2

Product Description :

Silicone Remover is a ready to use gel based on natural solvents which is used for removing polymerized silicone, MS Polymers, Acrylic Sealants and Polybutene Sealants.

Characteristics :

- Quick action
- Does not drip
- Pleasant citric smell

Applications :

- Removal of old sealant joints or spilt cured from different substrates
- Removing of silicone rests from of old joints before resealing
- Removing of sealant stains

Packaging and Colours :

Colours : Clear
Packaging : Plastic pot of 100 ml

Shelflife :

One year in unopened packaging in a cool and dry storage place at temperatures between + 5°C and +25°C.

Technical Data :

Base : Mixture of natural solvents and terpens
Consistency : Stable gel
Solvability : Does not dissolve in water
Does dissolve in carbohydrogens

Surfaces :

Substrate : Coated metals, ceramic tiles, laminate, painted substrates, glass, aluminium, some plastics - **Do not apply on Nylon**
State of Surface : Dry
Preparation : Not required

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.



SILICONE REMOVER

Date:01/02/05

Page 2 of 2

Application :

- Remove as much silicone rests as possible with a cutter
- Apply a layer of silicone remover with the brush
- Leave to penetrate for 10-15 minutes
- Remove silicone stains with a scraper dry towel and check if no silicone rests remain
- If necessary, repeat application
- Remove residues with warm water and detergent
- A new sealant layer can be applied after the substrate has dried completely.

Transport Information :

Road :	ADR :	3.31c
Maritime :	IMDG :	Free
Air :	ICAO/IATA-DGR :	Free
UN Number :		None

Labelling :

Symbol :	Xi - Irritating
R-Sentences :	10 – flammable / 38 – irritating for skin
S-Sentences :	2 – keep out of reach of children / 21 – Do not smoke during application

Safety Measures :

- Apply the usual industrial hygiene

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.