



TILE ADHESIVE

Date:22/04/05

Page 1 of 2

{PRIVATE }

Product Description :

Tile Adhesive is a ready to use adhesive paste for the bonding of wall and floor tiles.

Characteristics :

- Ready to use paste
- High adhesive strength
- Elastic
- Waterproof
- Non-flammable

Applications :

- Glueing of all wall- and floor tiles
- Glueing of floor tiles, even in rooms with floor heating
- Glueing of tiles on tiles
- Glueing of wall tiles, horizontal and vertical
- Placing of mosaique mats
- Especially suited for placing of tiles in kitchens and humid places
- Suited for glueing on "moving surfaces"

Packaging and Colours :

Colours : Light Yellow
Packaging : Cartridges of 300 ml, pots of 1 kg, buckets of 5 and 15 kg

Shelflife :

24 month in unopened packaging at temperatures between +5°C and +25°C.

Technical Data :

Base : Plastic dispersion
Consistency : paste
Curing System : Physical drying
Open Time *: 15 minutes
Drying Time *: Approx. 24 hours
Bonding Strength : 3.0 N/mm² (DIN 18156)
Specific Gravity : 1.6 g/ml
Temperature Resistance : -20°C to +70°C
Solids content in % : 87
Quantity to be applied : 1000 - 1500 g/m²

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.



TILE ADHESIVE

Date:22/04/05

Page 2 of 2

Surfaces :

Substrate : Porous surfaces such as stone, concrete, plaster, wood; old tiles
State of Surface : Clean, dry, dust- and greasefree
Preparation : Prepare very porous surfaces with a Primer
It is advised to do first an adhesion test on each surface

Application :

Application Method :

Apply adhesive with an adhesive comb with wide teeth (at least 5 mm) on a surface which can be covered within 10 min. Slide in tile and press on with strength.

Application Temperature: +5°C to +30°C

Clean with : Water

Repair with : Tile Adhesive

Transport Information :

Non hazardous for all means of transport

Labelling :

No hazardous labelling required

Safety Measures :

Apply the usual industrial hygiene.

Remarks :

24 hours after application the joints may be sealed with a joint sealant.
If glueing tile on tile in a humid atmosphere, wait at least 48 hours before filling the joints.
Always check whether the glue has dried completely before filling the joints.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.